

CLASS 1

Building Product Information Sheet

Product name:

Bevelled Architrave 40 x 12

Brand:

ECOEDGE

Product Code:

MDFUPBA04012

Product description and its intended use:

40 x 12 Bevelled Arch Painted MDF (5.4)

The bevelled architrave is a popular simple, modern architrave

Interior use - pre-primed to help reduce preparation time

Species	MDF	Primer	Primed
Grade	Premium moisture resistant Medium-Density Fibreboard		
Treatment	Untreated		

Place of manufacture: Made in New Zealand

Legal and trading name of the manufacturer(s):

Southern Pine Products Limited

Legal and trading name of the importer (if applicable):

N/A

Address for service:

635 Halswell Junction Road, Hornby South
Christchurch 8042, New Zealand

Website: www.sppnz.co.nz

Email: info@sppnz.co.nz

Phone: 0800 999 321

NZBN: 9429000023917

Relevant Building Code clauses:

B2 Durability Solution B2/AS1 and verification methods (VM) as specified in AS/NZS1604.2021
B2.3.1. (b) Internal use only. Treatment not required as stated in NZS3602:2003
F2 Hazardous Building Materials
F2.3.1 Flash-off requirements associated with the paint coating have been met (EO)

Statement on how the building product is expected to contribute to compliance:

B2 Durability - the products shall meet the requirements of Clause B2 of the Building Regulations 1992, Schedule 1 of the Building Code, in particular clause B2.3.1(a) - the life of the building, being not less than 50 years.

Limitations on the use of the building product:

ECOEDGE MDF is not intended for exterior use and must not be used in situations where it will be exposed to the risk of regular wetting or high humidity

Design requirements that would support the use of the building product:

When used in construction, particularly work deemed to be Restricted Building Work (RBW) as defined in the Building (Definition of Restricted Building Work) Order 2011 it's use should be in accordance with the specifications set out in NZS3604:2011 Timber framed buildings or NZS/AS1720 Part 1:2022 Timber structures.

Installation requirements:

As with all wood and timber based products, exposure to dust from this product may cause irritation to the eyes, respiratory system and skin via inhalation or skin contact. Use full PPE equipment included dust mask to AS/NZS 1716 standard and eye protection.

Maintenance requirements:

We recommend using a coating of either paint, oil or stain to extend the life of the product. Refer to ECOEDGE Installation Care and Maintenance Guide

Is the building product/building product line subject to warning or ban under section 26?:

No

Date: 6/12/2023