

Building Product Information Sheet

Product name:

CLASS 1

Bevelled	Architrave 60 x 18
Brand:	
ECOEDO	je
Product C	ode:
MDFUPB.	A06018
Product d	escription and its intended use:
60 x 18 E	Bevelled Arch Painted MDF (5.4)
The beve	elled architrave is a popular simple, modern architrave
Interior u	use - pre-primed to help reduce preparation time
Species Grade Treatme	MDF Primer Primed Premium moisture resistant Medium-Density Fibreboard ent Untreated
Place of n	nanufacture: Made in New Zealand
_egal and	trading name of the manufacturer(s):
Southerr	n Pine Products Limited
_egal and	trading name of the importer (if applicable):
N/A	
Address f	or service:
	lswell Junction Road, Hornby South hurch 8042, New Zealand
Website:	www.sppnz.co.nz
Email:	info@sppnz.co.nz
Phone:	0800 999 321
NZBN:	9429000023917
IN IN	INISTRY OF BUSINESS, NOVATION & EMPLOYMENT GNA WHAKATUTUKI

BRM 8582 03/23

Relevant Building Code clauses:

B2 Durability Solution B2/AS1 and verification methods (VM) as specified in AS/NZS1604.2021

- B2.3.1. (b) Internal use only. Treatment not required as stated in NZS3602:2003
- F2 Hazardous Building Materials
- F2.3.1 Flash-off requirements associated with the paint coating have been met (EO)

Statement on how the building product is expected to contribute to compliance:

B2 Durability - the products shall meet the requirements of Clause B2 of the Building Regulations 1992, Schedule 1 of the Building Code, in particular clause B2.3.1(a) - the life of the building, being not less than 50 years.

Limitations on the use of the building product:

ECOEDGE MDF is not intended for exterior use and must not be used in situations where it will be exposed to the risk of regular wetting or high humidity

Design requirements that would support the use of the building product:

When used in construction, particularly work deemed to be Restricted Building Work (RBW) as defined in the Building (Definition of Restricted Building Work) Order 2011 it's use should be in accordance with the specifications set out in NZS3604.2011 Timber framed buildings or NZS/AS1720 Part 1.2022 Timber structures.

Installation requirements:

As with all wood and timber based products, exposure to dust from this product may cause irritation to the eyes, respiratory system and skin via inhalation or skin contact. Use full PPE equipment included dust mask to AS/NZS 1716 standard and eye protection.

Maintenance requirements:

We recommend using a coating of either paint, oil or stain to extend the life of the product. Refer to ECOEDGE Installation Care and Maintenance Guide

Is the building product/building product line subject to warning or ban under section 26?: $\ensuremath{\mathsf{No}}$

Date: 6/12/2023